

Elastic waterproofing for floor and wall crack bridging

PRODUCT

weberdry flex is a ready to use one component product, based on an elastomeric acrylic paste with co-polymer resins. It can be used on properly prepared surfaces such as concrete, masonry. It is mainly used to cover hairline cracks and visibly open cracks.

It is possible to over-coat existing coatings on a mineral or synthetic resin base that are well adhered and in good condition.

weberdry flex forms a protective and decorative film with permanent elasticity and excellent adhesion.

weberdry flex shows an exceptional resistance to extreme weather conditions. It is non-toxic and environmental friendly.

CHARACTERISTICS

Colors	The product is available in 2 colors (white and brick)
Paste density	1.150
pH	11
Elongation at break	≈ 400%

INSTRUCTIONS FOR USE

SUBSTRATE PREPARATION

Substrate must be clean, sound and free from greasy matters and dust. Remove all traces of paint, mould oil which may affect the adhesion. Before the application the substrate must be sufficiently cured in a way that any shrinkage has already occurred. All imperfections, cracks must be repaired using suitable materials from our range of products before application of **weberdry flex**.

PRODUCT APPLICATION

weberdry flex is applied using cotton roll or brush. It is usually required to apply two coats to obtain satisfactory results.

CONSUMPTION

7m² / per 4 Kg pail / per coat.

STORAGE

6 months after manufacturing date in its original packing non open, protected form frost and heat.

SAFETY PRECAUTIONS

Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting. In both cases seek medical attention. The product is non-flammable.



PACKAGING

Leb	Syria	Jordan	UAE	Qatar	Kuwait	KSA	Oman
4 kg	4 kg	4 kg	-	-	-	-	-
18 kg	18 kg	18 kg	-	-	-	-	-

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

PG:29