

Acrylic water based sealer and dust proofer

PRODUCT

weberfloor sil 241 WB is a water based, penetrating acrylic sealer and dust-proofer. It is based on hard resins that provide a durable and serviceable finish with excellent adhesion to concrete floors, stamped concrete or natural stones. It allows conserving the original color of the support. This acrylic sealer offers high exterior durability and UV, alkali and water resistance.

SCOPE OF USE

- Terraces
- Private parking
- Shopping centers
- Show rooms
- Warehouses

CHARACTERISTICS

Color	Milky white
Density	0.95
Touch dry	1 hour

INSTRUCTIONS FOR USE

SUBSTRATE PREPARATION

Substrate must be clean, sound and free from greasy matters and dust. Remove all traces of curing compounds, old paints and sealer, and debris which may affect the adhesion. Before the application the substrate must be sufficiently cured in a way that any shrinkage has already occurred. New concrete must be at least 28 days old with open pores.

Allow the concrete to completely dry before starting the application.

weberfloor sil 241 WB can be applied on stamped concrete once it is completely dried. Depending on the weather conditions, allow a period between 3 to 7 days before applying the sealer.

PRODUCT APPLICATION

weberfloor sil 241 WB is applied using a roller, a brush or an airless spray gun.

Two layers are recommended at half hour interval.

Allow to dry for few hours before exposure to traffic.

CONSUMPTION

0.117 litres/m²

STORAGE

One year after manufacturing date in its original



PACKAGING

Leb	Syria	Jordan	UAE	Qatar	Kuwait	KSA	Oman
20 Lit	20 Lit	20 Lit	20 Lit	20 Lit	20 Lit	20 Lit	20 Lit
25 Lit	25 Lit	25 Lit	25 Lit	25 Lit	25 Lit	25 Lit	25 Lit
200 Lit	200 Lit	200 Lit	200 Lit	200 Lit	200 Lit	200 Lit	200 Lit
1000 Lit	1000 Lit	1000 Lit	1000 Lit	1000 Lit	1000 Lit	1000 Lit	1000 Lit

packing non open, protected from frost and heat.

SAFETY PRECAUTIONS

Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning thoroughly with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting. In both cases seek medical attention. The product is non-flammable.

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of weber. The unauthorized disclosure, use,

dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

PG:22