

## Ready to use paintable putty

### PRODUCT

**weberpremix putty** is a ready to use water-based ready-mixed paintable skimming compound used for plaster walls and ceilings, filling cracks and flattens the unevenness surface to provide a smooth high quality finishing. **weberpremix putty** is a skimming compound can be coated with water-based coating application.

### ADVANTAGES

- Excellent adhesion to the concrete substrate
- Extra white
- Scratch resistant
- Sandable and paintable
- Correcting imperfect concrete surface or cement/sand plaster before painting
- Single component - ready and easy to use
- Non-asbestos
- Smooth and superior finish
- Applicable on Gypsum board

### CHARACTERISTICS

Color	White
Density	1.65 ± 0.05
Drying time	Within 30 min at 25 °C
Coverage	1.7 kg/m <sup>2</sup> for 1 mm thickness
Consumption	2 coats (new coat should be applied after drying of the first coat)

### INSTRUCTIONS FOR USE

#### SUBSTRATE PREPARATION

Substrate must be clean, sound and free from greasy matters and dust. Remove all traces of paint, mould oil which may affect the adhesion.

#### PRODUCT APPLICATION

The best way to smoothen a plaster wall or ceiling surface is by skim-coating it. Skim-coating is the technique of applying thin layers of **weberpremix putty** over the entire surface. Apply first layer of **weberpremix putty** thick at the required thickness between 1 to 5 mm. The material is hand applied by spreading it thin with a wide taping knife.

The number of layers is dependent on the surface roughness/unevenness. After the material is dried, **weberpremix putty** can be painted.



### PACKAGING

Leb	Syria	Jordan	UAE	Qatar	Kuwait	KSA	Oman
25kg	-	-	-	-	-	20kg	-

### CLEANING OF TOOL

Clean tools immediately after each use with warm water then wipe the tool surfaces dry to prevent rust left over compound should be sealed and stored appropriately.

### STORAGE

6 months after manufacturing date in its original packing non open, protected from frost and heat.

### SAFETY PRECAUTIONS

The product contains cement powders which, when mixed with water, release alkalis that could be harmful to the skin. It is preferable that the application be done in a ventilated area, and to wear protective gear for hands, eyes and respiratory system and to avoid breathing of the dust. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting, in both cases seek medical attention. The product is non-flammable.

### DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the

company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

## NOTE

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL (previously SODAMCO Holding). The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.