

## Ready mixed spatterdash slurry coat

### PRODUCT

**weberpremix key coat** is a ready mixed mortar based on mineral bonding agent used for preparing cement based surfaces before rendering. It improves the adhesion of the new plaster, cement & gypsum based. It is applied on internal or external walls and ceilings, fair faced concrete, masonry blocks, and old cement based plaster.

### CHARACTERISTICS

Appearance	Brownish granular powder
Composition	Portland cement, selected sand, additives
Grain size	0 to 4 mm
Resistance to fire as per BS EN 998 -1	Class A1

### APPLICABLE STANDARDS

BS 5262: 1991  
BS 5492: 1990  
BS 4551: Part 2: 1998  
ASTM C 150  
ASTM C 926  
ASTM C 897  
DTU 26.1  
DTU 20.1  
DTU 23.1

### INSTRUCTIONS FOR USE

#### SURFACE PREPARATION

Substrates must be sound, clean, dust free and free from all traces of oil, curing compound, gypsum, paint or laitance. The support must be dampened a few hours before the application of **weberpremix key coat**.

#### PRODUCT PREPARATION

Mix a 50 kg bag with 9 to 10 liters of clean cool water in order to obtain the consistency desired.  
For specific cases, when an important adhesion is required, 1 kg of **wberad 240 LTX** can be added to the mixing water.  
Mixing has to be done with an electric mixer.

#### PRODUCT APPLICATION

Apply the Premix.key coat using a tyrolean box or a power spray gun.

### CURING

Protect the newly applied plaster from sunshine and wind. The new plaster has to be cured with water for at least three days by spraying 3 to 4 times daily.



### PACKAGING

Leb	Syria	Jordan	UAE	Qatar	Kuwait	KSA	Oman
50 kg	50 kg	50 kg	-	-	-	-	-

### CONSUMPTION

Between 5 to 6 kg/m<sup>2</sup>, depending on the substrate and the application method.

### STORAGE

12 months after manufacturing date in original and non-open packaging, under cover, in dry condition, away from humidity, protected from extreme temperatures and direct sunlight.

### SAFETY PRECAUTIONS

The product contains cement powders which, when mixed with water, release alkalis that could be harmful to the skin. It is preferable that the application be done in a ventilated area, and to wear protective gear for hands, eyes and respiratory system and to avoid breathing of the dust. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting, in both cases seek medical attention. The product is non-flammable.

### DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the

company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

## NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

PG: 30

\*\*Available only in MENA